



## **crown head™ II**

Crown head dependability, quiet design reduces noise.

Diaphragm intake pump will not be damaged by running dry.

**Crown Head II a reliable, mid-priced electric macerating toilet.**

### **Freshwater Solenoid Model (C2F\*)**

- Whisper Flush<sup>sm</sup> design for quiet operation
- Less maintenance and odors than raw water models

### **Remote Intake Pump Model (C2R12 or C2R12)**

- Diaphragm intake pump can be run dry without damage
- Reduces noise levels
- Easier access to intake pump

### **All Crown Head II Models**

- Suitable for the most demanding boaters in any size vessel
- Proven, dependable design (same efficiency as the crown head)
- Efficient flushing action – includes powerful centrifugal macerating pump
- Simple and flexible installation for mounting above or below waterline
- Easy to clean and maintain
- Pump cover that neatly hides components
- Remanufactured pump exchange program available
- Can be used with on-board treatment systems (such as the Lectra/San<sup>®</sup>) and/or holding tanks
- Each unit is assembled by hand, individually tested and backed by Raritan's one-year Limited Warranty and legendary technical support team

### **Options**

- Available for 12, 24, 32V DC or 120/240V AC
- Choice of full-size household-style bowl or marine-size bowl
- Available in white or bone

*Raritan products are chosen by powerboat, sailboat, houseboat, and RV owners and manufacturers the world over for their dependability, environmental responsibility, simplicity of installation, operation, and maintenance. The product line includes house-hold style toilets, marine toilets, marine sanitation devices and systems, cleaning products, icemakers, water heaters, and rudder angle indicators.*

*To view our complete line, to obtain installation and servicing guides, visit [raritaneng.com](http://raritaneng.com).*

**THE MOST DEPENDABLE NAME ON THE WATER**




# crown head™ II

Height:  
17 3/8" (44.1cm)  
Household  
17" (43.2cm)  
Marine

Bowl Width:  
14 3/8" (36.6 cm)  
Household  
13" (33 cm)  
Marine


Base Width:  
10 1/2" (26.8cm)



Bowl Depth:  
19 1/4" (48.9cm)  
Household  
16 3/4" (42.6cm)  
Marine

Base Depth:  
10 7/8" (27.7cm)

## Crown Head II Using Sea Water and Connected to a Lectra/San




The advanced crown head II was designed without compromising the high level of efficiency of the crown head. This was accomplished by redesigning the way water is delivered to the bowl. The raw water model uses a remote-mounted pump, while the on-board pressurized freshwater model is connected to the pressurized water system. As a result, the boater benefits from the same level of performance with quieter operation.

A newly designed pump cover blends with the porcelain bowl, creating a streamlined one-piece look. This cover neatly hides all the components while at the same time allows immediate access to the macerator and discharge pump.

The crown head II is built of the highest quality materials, is reliable and easy to maintain.

### Optional Control



The crown head II optional control allows for selection of momentary operation or independant operation of incoming water and macerator.

### Specifications

Units Voltage	Intake pump Models	Freshwater Solenoid Model
	Amp draw @ nominal voltage	Amp draw @ nominal voltage
12 VDC	28	19
24 VDC	14	9.5
32 VDC	11	7.5

**Additional parts required:** Fuses or circuit breakers, wire terminal ends, four stainless steel mounting bolts (minimum 1/4" [6mm]) or lag screws and washers, 1 1/2" (38mm) I.D. sanitation hose, and 3/4" (19mm) I.D. sanitation hose and hose clamps. For pressurized fresh water flushing, a manual ball valve (3/4" IPS) is also recommended.

**Approximate Shipping Weight:** 60 lbs (27 kg)

### Product Models

C2 Crown head II	Straight Discharge (standard)	Bowl Color	Remote Intake pump (standard)	Specify	
				12	24
9	90 Discharge	A White bowl, marine-size (standard)	F Freshwater Solenoid	32	120/240
		W White bowl, household-style		24T	

To order the correct unit for your installation make one selection from each column above.

#### Model samples:

C2912 - Crown Head II, white bowl marine size, 90° discharge 12V

C2WF12 - Crown Head II, white bowl household-style, freshwater solenoid, 12V

Additional models are available. Call Raritan Technical Support for assistance in ordering the model that best suits your application.

#### For more information contact:

Raritan Engineering Company Inc.  
530 Orange Street  
Millville, NJ 08332, USA  
Telephone: 856-825-4900  
Fax: 856-825-4409  
e-mail: info@raritaneng.com

#### raritaneng.com

Southern Plant and Office  
3101 SW 2nd Avenue  
Ft. Lauderdale, FL 33315 USA  
Telephone: 954-525-0378  
Fax: 954-764-4370



L1006 1006kgs

**THE MOST DEPENDABLE NAME ON THE WATER**